TECHNICAL NOTES

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

No. 398

THE EFFECT OF SLOTS AND FLAPS ON THE LIFT

AND DRAG OF THE McDONNELL AIRPLANE AS

DETERMINED IN FLIGHT

By Hartley A. Soule
Langley Memorial Aeronautical Laboratory

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

TECHNICAL NOTE NO. 398

THE EFFECT OF SLOTS AND FLAPS ON THE LIFT AND

DRAG OF THE McDONNELL AIRPLANE AS DETERMINED

IN FLIGHT

By Hartley A. Soulé

Summary

This note contains the results of flight tests con-
ducted by the National Advisory Committee for Aeronautics on
a low-wing monoplane equipped with leading-edge slots ex-
tending over the entire wing and flaps extending only to the
ailerons, to find their effect on the lift and drag character-
istics of the airplane. Curves are given showing the lift
and drag characteristics of the airplane for the following
conditions of the slots and flaps: slots closed and flaps
neutral; slots open and flaps neutral; slots closed and
flaps down; and slots open and flaps down. In addition, the
high and low speeds in level flight and the climbing char-
acteristics are given.

The results show that the slots used alone increase
the maximum lift coefficient 54 per cent; the flaps alone
increase it 38 per cent; and the slots and flaps in combi-
nation give a total increase in lift coefficient of 94 per
cent. The slots and flaps in combination decrease the land-
ing speed from 60 to 43 m.p.h.; increase the speed range of
the airplane 40 per cent; and increase the glide angle at
landing speed 4.2°.

Introduction

It is generally recognized that one of the most impor-
tant problems now confronting aeronautical engineers is to
improve the airplane in such a manner as to increase the
safety of flight. The National Advisory Committee for Aero-
nautics has realized this and is now engaged in a very ex-
tensive program of research, including both wind-tunnel and

flight testing, for the express purpose of increasing the safety of airplanes.

From the standpoint of the aerodynamics of the airplane, it appears that the most promising immediate line of attack is to find means of decreasing the landing and take-off speeds and of providing adequate control and stability at the attitudes corresponding to these speeds. Because of their known ability to increase the maximum lift coefficient, slots and flaps present one very promising method of accomplishing this object.

As a part of its general research on safety, the Committee has therefore undertaken to investigate the aerodynamic, performance, landing, take-off, stability, maneuverability, and control characteristics of an airplane equipped with slots and flaps so that the influence of these devices could be appraised, not only with respect to safety but also with regard to performance in general. This investigation is now in progress on the McDonnell airplane, which was originally designed for entry in the Daniel Guggenheim Safe Aircraft Competition. Some preliminary information, the presentation of which is the object of this report, has been obtained to date.

These preliminary data consist of lift and drag characteristics; slot behavior or operation; and certain performance data, including minimum speed, high speed, glide angles, and climb characteristics. These results were obtained, in general, with four combinations of slot and flap setting; slots open and closed, with flaps neutral; and slots open and closed, with flaps depressed. Measurements were made according to methods commonly in use by the Committee.

The Airplane

A three-view drawing and photographs showing the general arrangement of the McDonnell airplane are given in Figures 1 to 4, inclusive. The principal features of the airplane are given in the following table:

Type - Low-wing tractor monoplane.
Seating arrangement - Two-place, tandem, open cockpit.

General Characteristics

span	- 35 ft.	over-all length	- 21 ft. 4 in.
chord (c)	- 5 ft. 8 in.	height	- 7 ft. 2½ in.
area[1]	- 196.5 sq.ft.	engine	- Warner "Scarab" rated 110 hp at 1,850 r.p.m.
aspect ratio	- 6.2	weight (test)	- 1,800 lb.
wing section	- M-6	power loading	- 16.3 lb./hp
dihedral	- 4.5°	wing loading	- 9.1 lb./sq.ft.

Slot and Flap Dimensions

span of auxiliary airfoil	31 ft. 7½ in.
chord of auxiliary airfoil	10.2 in.; 15% c.
span of flaps	22 ft. 4-1/8 in.
chord of flaps	17-7/6 in.; 25.6% c.
flap angle when fully depressed[2]	-40°

Location of Auxiliary Airfoil with Slot Open
(See fig. 5.)

width	5.43 in.; 8% c.
depth	2.38 in.; 3.5% c.
gap	1.02 in.; 1.5% c.

The auxiliary, or leading-edge, airfoil is divided into four sections along the span, two on each side of the fuselage. Normally, these auxiliary airfoils are automatic in action, although, in order to allow testing with slots

---

[1] The area was computed to include the projected plan area of the fuselage bounded by the wing roots and the leading and trailing edges extended. Thus it differs from that published elsewhere, viz., 180 sq.ft.

[2] Value given is that used in tests. Flaps designed for 50° travel but air loads prevent full movement in flight.

opened or closed at all angles of attack, means were pro-
vided to lock them in either the full-open or closed po-
sition.

The flaps extend along the entire trailing edge with
the exception of the part occupied by the ailerons and are
manually operated from the pilot's cockpit. They are inter-
connected with the stabilizer. Means are provided, however,
for adjusting the stabilizer independently of the flaps.

The airplane, as originally designed and constructed,
was equipped with wheel fairings, landing-gear strut fair-
ings, and N.A.C.A. cowling. These items were not included
when the airplane was delivered to the Committee, and the
subject tests were made without them.

Tests and Test Methods

A complete description of the methods and apparatus
used in these tests will be given in a later report deal-
ing with the complete investigation. Only a brief descrip-
tion of the method is given here.

Lift and drag characteristics.- The lift and drag
characteristics were measured for each of the following
slot and flap arrangements:

1. Slots closed and flaps neutral.
2. Slots open and flaps neutral.
3. Slots closed and flaps down.
4. Slots open and flaps down.

The characteristics were determined by means of glide
tests, which are described in detail in reference 1. Brief-
ly, the glide-test procedure is as follows:

The airplane is flown in a steady glide with the pro-
peller operating approximately at V/nD for zero thrust.
During the glide, simultaneous records are taken of the
flight-path angle, the indicated air speed, the angle of
inclination of the wing chord, the engine speed, and the
temperature and pressure of the air at the altitude of the
airplane. The weight of the airplane during the glide is
known. From the weight, and the flight-path angle, the com-
ponents of force acting perpendicular to and parallel to the
flight path are calculated. The indicated air speed is
corrected to true air speed by means of the pressure and

temperature data. Propeller thrust is calculated from the
r.p.m., the true air speed, air density, and propeller
characteristics. The drag component, as calculated from
the weight and flight-path angle, is then corrected for the
component of thrust acting along the flight path, and also
for the drag of the apparatus used to measure flight-path
angle and air speed. Similar corrections to the lift com-
ponent are neglected.

From the lift and corrected drag components thus
found, the corresponding coefficients are calculated ac-
cording to the relations,

$$C_L = \frac{L}{q\,S}$$

and,

$$C_D = \frac{D}{q\,S}$$

in which the symbols have their standard significance. An-
gle of attack is taken as the difference between the angle
of the flight path and the angle of inclination of the wing
chord.

Slot operation.- The angle of attack at which the slot
starts to open was determined by flying the airplane at
high speed and then slowly increasing the angle of attack
until the auxiliary airfoils began to move out. Records
of the air speed and angle of attack were obtained at this
point with the same apparatus used in the glide tests. The
angle of attack was then further increased until the aux-
iliary airfoils reached the full-out position. At this
point, records were again taken. The slot operation was
determined both with the flaps neutral and with the flaps
depressed.

Performance.- The performance characteristics measured
consisted of the minimum speed in level flight, minimum
speed in a glide, high speed, glide angle at minimum speed,
minimum angle of glide, and rates and angles of climb.

For the measurement of the minimum speed in level
flight and minimum speed in glide the same apparatus used
in the glide tests was utilized, the only additional in-

strument required being a sensitive indicating altimeter
to enable the pilot to maintain true level flight when
required.

    .. The high speed was determined for two conditions,
namely, slots open, and slots closed; the flaps were neu-
tral in each case. This determination was accomplished
by timing the airplane over a measured speed course. Three
runs were made in each direction for each condition, and
the results for the six runs averaged. No corrections
were made to standard atmospheric conditions, as the cor-
rection to the engine horsepower practically compensates
for the correction to the air speed.

    Climb characteristics were obtained for each slot and
flap combination by measuring the air speed and flight-
path angle in a series of climbs at different speeds, start-
ing from 100 feet altitude.

    Minimum angle of glide and glide angle at minimum
speed were obtained as incidental results of the other tests

Precision

    The instruments used in these tests are capable of
measuring angles of the flight path and attitude of the air-
plane to within $0.1°$, and air speed within 1 per cent.
(Reference 2.) Such errors introduce approximately a 1
per cent error in the drag, and an inappreciable error in
the lift. However, although all flights were made under
the best obtainable air conditions, a small degree of at-
mospheric turbulence existed at all times. This insta-
bility in the atmosphere, in addition to a small but ap-
preciable tendency for the airplane to oscillate, caused
slightly irregular records of the angles measured, which
are reflected in the dispersion of points in the results.
The accuracy of the results is therefore somewhat reduced.
It is estimated that lift and drag coefficients are cor-
rect to within ± 3 per cent, and angle of attack to within
$\pm 0.3°$.

    The maximum and minimum speeds are correct to within
± 1 per cent. Angles of climb are estimated to be correct
to within $\pm 0.2°$, and the rate of climb to within ± 3 per cent.

Discussion of Results

The results of the tests are given in Figures 6 to 15,
and in Tables I and II. Figures 6 to 13 give the results,
with experimental points, of the lift and drag measurements
for the various slot and flap combinations. These results
are presented as curves of lift and drag coefficient and
L/D against angle of attack, and also in the form of polar
curves. To facilitate comparison of the results with the
different slot-flap combinations, the curves of C_L and C_D
against α for all cases have been reproduced, without
the experimental points, in Figure 14. For the same reason,
the polars have been grouped in Figure 15. The data from
which the lift and drag curves were obtained are given in
Table I.

Table II gives the results of the performance and slot-
operation tests.

The lift and drag characteristics.- Referring to Fig-
ures 14 and 15, it will be noticed that in all cases the
lift coefficient is still increasing when the curves are
discontinued. This circumstance could not be avoided,
because of the instability of the airplane at the higher
angles of attack, and the consequent inability of the pi-
lot to maintain steady conditions long enough to take rec-
ords at these angles of attack. It is probable that the
instability at high angles of attack was caused by a par-
tial stall of the wings (burble at the center portion) so
that when instability was encountered the airplane was
operating very close to its maximum lift. Consequently
the values given for the maximum lift coefficients (highest
points on the lift curves) are believed to be not more than
3 per cent lower than the true maximum lift coefficient.

With slots closed and flaps neutral, corresponding
to the condition of no slots or flaps, the airplane has
a maximum lift coefficient of 1.00 and a minimum drag co-
efficient of 0.08. The maximum lift coefficient compares
favorably with the maximum lift coefficient of 1.113 ob-
tained in the N.A.C.A. propeller-research tunnel on a 2-
foot by 12-foot model of the M-6 airfoil, and at a Reynolds
Number of about two-thirds that of the present tests.
(Reference 3.) The difference between the two values is
explained by the discontinuities in the wing surface of
the airplane, caused by slot and flap installation, and

by the presence of the fuselage in the case of the airplane
which makes close comparisons invalid. The minimum drag
coefficient, 0.08, is rather high, compared with an average
value of 0.06 for conventional airplanes in the same class.
In this connection, however, the lack of landing-gear strut
fairings, wheel fairings, and engine cowling during the
tests, should be borne in mind.

In the following discussion of the improvements of
the lift and drag characteristics obtained through the use
of slots and flaps all comparisons are made with the con-
dition of slots closed and flaps neutral. It should be
realized that the results obtained by the use of slots
and flaps will be different with different airfoils and
that the percentages given cannot be taken as represent-
ing the increase to be expected from the installation of
slots and flaps on any wing section.

With slots open and flaps neutral, the stall was de-
layed 11°, and the maximum lift coefficient was increased
to 1.54, or 54 per cent. This increase represents a 19
per cent reduction in landing speed. On the other hand,
the minimum drag coefficient with slots locked open was
increased 10 per cent. This means that the sacrifice of
the movable or automatic feature of the slots, in favor
of simplified construction, with slots of this type, would
require a 10 per cent increase in power to maintain the
speed range possible with the slots automatic.

With slots closed and flaps down, the maximum lift
coefficient was increased from the basic value of 1.00 to
1.38, or 38 per cent. At the same time, the angle of at-
tack of maximum lift coefficient was lowered 2° from the
original value, and the angle of zero lift was lowered 6°.
Although the minimum drag was greatly increased with flaps
down, no significance is attached to this result, as there
is no reason for using the flaps at the low angles of at-
tack.

With slots open and flaps down, the maximum lift co-
efficient reached its highest value, 1.94. It is of in-
terest to note that the sum of the increases in $C_{L_{max}}$
resulting from the use of slots and flaps separately is
92 per cent, as compared with the total increase of 94 per
cent when the slots and flaps are used together. This re-
sult would indicate that the effects of slots and flaps
are almost independent of one another.

In considering the possible use of auxiliaries such as slots and flaps to decrease the landing speed, it is worth while to analyze the drag at maximum lift, with regard to its effect on the power-required to maintain level flight. Such an analysis has been made for the several slot-flap combinations of the subject tests, using the formula,

$$\frac{P}{P_o} = \frac{C_D}{C_{D_o}} \left(\frac{C_{L_{o_{max}}}}{C_{L_{max}}}\right)^{3/2}$$

where,

    P   - power required for minimum speed level flight with auxiliaries.

    P_o - power required for minimum speed level flight without auxiliaries.

    C_D - drag coefficient at maximum lift with auxiliaries.

    C_{D_o} - drag coefficient at maximum lift without auxiliaries.

    C_L - maximum lift coefficient with auxiliaries.

    C_{L_o} - maximum lift coefficient without auxiliaries.

The results of this analysis follow.

With slots alone, the increase from the basic condition in power required to maintain minimum horizontal speed is 8 per cent. With flaps alone, there is a decrease of 12 per cent. With slots and flaps together, the decrease is 4 per cent. This is an apparently favorable result. However, since the minimum speed is lowered 28 per cent with slots and flaps, there is a corresponding approximate 5 per cent decrease in the ratio V/nD at which the propeller operates, with a consequent reduction in propeller efficiency. Computations based on average propeller data show that the efficiency of the propeller is decreased by about 20 per cent, with a 5 per cent reduction in V/nD in the low-speed range. The power available at maximum C_L may therefore not be sufficient to maintain level flight when using slots and flaps, unless steps are taken to increase the propeller efficiency at low speeds.

An inspection of the curves of Figures 7, 9, 11 and 13 shows that the maximum L/D is 5.8, a value which compares unfavorably with the average value of 8 for conventional airplanes. Here again, however, the absence of important fairings during the tests must be considered. Figures 7 and 9 also show that the maximum L/D with slots open and flaps neutral is the same as with slots closed and flaps neutral. Thus, it does not matter a great deal whether the auxiliary airfoil opens below or above the angle of maximum L/D for the unslotted wing.

Performance.- For the weight and drag as flown the airplane is somewhat underpowered as evidenced by the low rate of climb, 310 feet per minute. As a result the performance as such is not impressive. However, for the purpose of these tests the performance itself is of minor interest, the chief interest being in the difference of performance obtained with and without the slots and flaps in operation as is discussed in the following paragraphs.

It will have been noted that the actual take-off and landing speeds were not measured. The reason for this was that a direct measurement would have required a calibration of the air-speed head mounted on the airplane, for which time was not available in this part of the investigation. With respect to the take-off speed, it so happens that the angles of attack at which the minimum speeds in level flight were attained with and without the slots and flaps in operation can be obtained with this airplane at take-off. It is possible, therefore, to use the minimum speeds in level flight for these conditions of slots and flaps as indicative of the corresponding take-off speeds, and they are used hereafter in place of the true take-off speeds. It is realized that this procedure does not give exact results because at take-off there must be some power available for climb and at minimum speed in level flight there is none, and also because of the influences of ground effect. However, it provides a satisfactory basis for the comparison of the effects of slots and flaps on take-off speed. With respect to the landing speed the minimum speed in a glide is the true landing speed for a landing which is made from a glide without leveling off, a type of landing which is entirely possible and is practiced with this airplane. The minimum speed in a glide is used in place of landing speed hereafter.

Without slots or flaps, the landing speed is 60 m.p.h. and the glide angle at this speed is 13°. Slots and flaps

reduce the landing speed to 43 m.p.h., and at the same time increase the glide angle to 17.3°. Thus, the slots and flaps have reduced the landing speed 17 m.p.h. and increased the angle of approach by 4° without increasing the vertical velocity. Without slots and flaps the take-off speed is 55 m.p.h. and with slots and flaps it is 40 m.p.h.

It is interesting to note that the minimum speed in level flight was 40 m.p.h. and occurred at an angle of attack of 16.7°, while the minimum speed in a glide was 43 m.p.h. and occurred at an angle of attack of 23.7°. The fact that a lower speed at a lower angle of attack was attained in the level flight condition is due to the slipstream effects. The fact that the highest angle of attack attained in level flight was 16.7°, while the maximum lift occurred at an angle of attack of 23.7°, shows that the airplane has insufficient power available to take full advantage of the use of slots and flaps to decrease the minimum speed in level flight. It follows that if the airplane had sufficient power to maintain level flight at maximum lift and had a higher landing gear so as to take off at a higher angle of attack it would be possible to appreciably decrease the take-off speed.

The high-speed runs with slots closed and slots locked open, indicate the effect of sacrificing the movable or automatic feature of the slots in favor of simplified construction. With slots closed, the high speed was 91.4 m.p.h., and with slots fixed open it was 84.8 m.p.h. This reduction of 6.6 m.p.h. in the high speed is probably sufficient justification for the use of the automatic or movable feature for this particular design of slot. It should be appreciated, however, that it is possible to design fixed slots which will not have such an unfavorable effect on high speed. (Reference 4.)

The speed ranges given in Table II are all based on the high speed with the slots closed and the flaps neutral. The low speeds used are those obtained in the glides, as they are more indicative of the wing improvement than the low speeds in level flight, where the propeller characteristics are a consideration. The use of slots and flaps increases the speed range 40 per cent, the slots accounting for a 25 per cent and the flaps a 17 per cent increase.

The results of the climb tests show nothing of particular interest, other than that the climb is poor.

To summarize, the results show that the slots used alone increase the maximum lift coefficient 54 per cent, the flaps alone increase it 38 per cent, and the slots and flaps in combination give a total increase in maximum lift coefficient of 94 per cent. The slots and flaps in combination decrease the landing speed from 60 to 43 m.p.h., increase the speed range of the airplane 40 per cent, and increase the glide angle at landing 4.2°.

Langley Memorial Aeronautical Laboratory,
    National Advisory Committee for Aeronautics,
        Langley Field, Va., October 13, 1931.

References

1. Green, M. W.: Determination of the Lift and Drag Characteristics of an Airplane in Flight. T.N. No. 223, N.A.C.A., August, 1925.

2. Thompson, F. L., and Keister, P. H.: Lift and Drag Characteristics of a Cabin Monoplane Determined in Flight. T.N. No. 362, N.A.C.A., January, 1931.

3. Wood, Donald H.: Tests of Large Airfoils in the Propeller Research Tunnel, Including Two With Corrugated Surfaces. T.R. No. 336, N.A.C.A., May, 1929.

4. Weick, Fred E., and Wenzinger, Carl J.: The Characteristics of a Clark Y Wing Model Equipped with Several Forms of Low-Drag Fixed Slots. T.R. No. 407, N.A.C.A., August, 1931.

√ Flight-path   *all negative*

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
Flight and run No.	Attitude angle λ deg.	Glide ang angle γ deg.	Angle of attack α deg.	Cos of gliding angle	Sine of gliding angle	Wt. during run, W, lb	Lift L lb.	Apparent drag, D₀, lb.	Dynamic pres. q lb/sq.ft.	Barometric pres. p in.Hg.	Air temperature, t °F	Spec. wt. of air gp lb/cu.ft.	True velocity V ft./sec.	Propeller speed n r.p.s.	V/nD	Thrust coefficient C_T	Thrust T lb.	Drag of suspend instrumt d lb	True drag D lb.	Lift coefficient C_L	Drag coefficient C_D
Slots closed and flaps neutral:																*Slots closed and flaps neutral*					
21-2	1.7	-11.0	12.7	.982	.191	1776	1740	339	9.42	-27.30	75	.0677	94.1	14.3	0.822	0.0035	7	10	330	0.943	0.178
3	-1.4	-10.4	9.0	.984	-.180	1764	1740	317	12.70				109.4	15.5	.875	-.001	-2	13	302	.700	.120
4	-3.0	-10.9	7.9	.982	-.189	1752	1720	331	13.90				114.5	16.7	.847	.001	3	14	320	.632	.117
5	-5.8	-11.5	5.7	.980	-.193	1740	1700	347	18.15				130.9	18.9	.857	.0005	1	15	333	.477	.093
6	-8.7	-13.0	4.3	.974	-.225	1728	1680	388	21.2				140.5	20.3	.860	.0	0	15	373	.409	.090
7	-11.0	-13.8	2.8	.971	-.238	1716	1660	408	25.0				153.3	22.1	.860	.0	0	16	392	.339	.080
22-1	2.1	-13.6	15.7	.972	-.235	1784	1730	419	8.74	27.30	75	.0677	90.7	13.1	.855	.0005	1	10	410	1.010	.238
2	2.2	-12.4	14.6	.977	-.215	1767	1730	379	9.10				92.5	13.5	.850	.001	2	10	371	.968	.206
3	2.1	-12.3	14.4	.977	-.213	1750	1710	372	9.10				92.5	13.4	.855	.0005	1	10	363	.956	.203
4	1.8	-11.4	13.2	.980	-.198	1733	1700	342	9.52				94.7	14.2	.825	.003	5	10	337	.910	.180
5	-.9	-10.4	9.5	.984	.180	1716	1690	308	11.5				104.2	15.4	.840	.002	4	12	300	.746	.132
6	-3.0	-10.6	7.6	.983	.184	1699	1670	312	13.9				114.5	16.8	.842	.0015	4	14	302	.610	.110
7	-5.0	-11.1	6.1	.981	.192	1682	1650	323	17.6				128.5	19.2	.820	.0035	12	15	320	.470	.093
32-1	2.6	-12.8	15.4	.975	.221	1797	1750	397	9.10	27.30	72	.0681	93.	13.2	.87	-.001	-2	10	385	.98	.215
2	1.9	-10.9	12.8	.982	.189	1788	1750	338	9.41				94.	13.9	.84	-.002	-3	10	331	.95	.179
3	.9	-10.2	11.1	.984	.177	1779	1750	314	10.03				97.	14.3	.84	-.002	-4	11	307	.89	.156
4	-.8	-10.2	9.4	.984	.177	1770	1740	313	11.34				104.	14.9	.85	-.001	-2	12	303	.77	.136
5	-2.4	-9.8	7.4	.985	.174	1761	1730	299	13.0				111.	15.5	.88	-.002	-4	13	282	.68	.110
6	-3.4	-10.0	6.6	.985	.174	1752	1730	305	13.8				114.	16.5	.85	.001	2	13	294	.64	.109
7	-3.4	-9.9	6.5	.985	.172	1743	1700	300	14.3				116.	17.9	.80	.006	17	14	303	.61	.108
8	-7.4	-11.4	4.0	.980	.198	1734	1700	345	18.5				132.	19.1	.86	.0	0	15	330	.47	.051
9	-10.2	-12.6	2.4	.976	.218	1725	1680	378	21.9				143.	20.4	.87	-.001	-4	15	359	.39	.083
10	-12.7	-14.4	1.7	.969	.249	1716	1660	427	25.6				155.	22.0	.87	-.001	-4	16	407	.33	.081
34-1	2.6	-12.6	15.2	.976	.218	1803	1760	393	9.10	27.30	70	.0683	93.	12.9	.89	-.003	-4	10	379	.98	.212
2	1.9	-10.8	12.7	.982	.187	1796	1760	336	9.41				94.	13.7	.85	.001	2	10	328	.95	.178
3	1.4	-10.7	12.1	.983	.185	1789	1760	331	9.94				97.	14.2	.84	.002	4	11	324	.90	.166
4	-.3	-10.1	9.8	.984	.175	1782	1750	312	11.02				102.	14.5	.87	-.001	-2	12	298	.81	.138
5	-2.0	-10.0	8.0	.984	.174	1775	1750	309	12.33				108.	15.4	.875	-.0015	-3	13	293	.71	.121
6	-2.6	-9.9	7.3	.985	.177	1768	1740	313	13.30				112.	16.5	.84	.002	3	13	305	.67	.116
7	-3.0	-10.0	7.0	.985	.174	1761	1730	306	13.9				115.	17.5	.81	.005	14	13	307	.63	.112
8	-7.4	-11.5	4.1	.980	.199	1754	1720	349	18.5				132.	18.7	.87	-.001	-3	15	331	.47	.081
9	-9.6	-12.7	3.1	.975	.220	1747	1700	384	21.9				143.	20.4	.87	-.001	-4	15	365	.40	.085
10	-11.9	-13.9	2.0	.971	.240	1740	1690	417	25.5				155.	22.0	.87	-.001	-4	16	397	.34	.079
Slots open and flaps neutral																*Slots open and flaps neutral*					
10-1	9.2	-13.0	22.2	.9744	.2250	1849	1800	416	6.55	27.30	77	.0675	79.0	12.4	.790	.006	8	8	416	1.40	.323
2	3.5	-10.3	15.8	.9839	.1788	1834	1810	328	8.27				88.7	13.7	.801	.0055	9	9	328	1.11	.198
3	4.0	-9.2	13.2	.9871	.1599	1819	1795	291	9.72				96.2	15.2	.783	.007	15	11	295	.939	.154
4	.7	-9.8	10.5	.9848	.1706	1804	1780	307	12.06				107.0	16.4	.809	.005	12	13	306	.748	.128
5	-1.8	-10.5	8.7	.9833	.1822	1789	1760	326	14.6				117.8	17.8	.810	.0045	13	14	325	.612	.113
6	-5.5	-12.1	6.6	.9778	.2096	1774	1730	372	18.6				133.0	20.4	.807	.005	19	15	376	.474	.103
7	-8.0	-12.8	4.8	.9751	.2215	1759	1715	389	21.4				142.7	21.7	.813	.004	17	15	391	.407	.093
8	-10.1	-14.3	4.2	.968	.2474	1744	1690	431	25.0				154.0	23.4	.815	.004	20	16	435	.344	.089
11-1	7.9	-14.1	22.0	.9690	.244	1780	1720	435	6.34	27.30	75	.0677	75.7	12.0	.777	.008	10	7	438	1.38	.351
2	3.7	-10.7	14.4	.9826	.1857	1768	1740	328	7.96				87.0	13.7	.785	.007	12	9	331	1.11	.212
3	1.1	-9.6	10.7	.9860	.1668	1756	1730	293	9.72				96.2	15.4	.775	.008	17	11	299	.906	.156
4	-2.4	-10.6	8.2	.9829	.1840	1744	1715	321	12.06				107.0	14.7	.900	-.004	-8	13	300	.723	.127
5	-4.6	-10.7	6.1	.9826	.1857	1732	1700	322	14.4				117.0	17.4	.835	.002	5	14	313	.602	.111
6	-7.5	-12.1	4.6	.9778	.2096	1720	1680	361	18.5				132.2	19.7	.830	.003	10	15	356	.463	.098
7	-10.3	-13.2	2.5	.9736	.2284	1708	1660	391	22.0				144.4	21.7	.824	.003	12	15	388	.384	.090
8	-13.4	-15.2	1.8	.9641	.262	1696	1635	445	25.0				154.0	23.2	.820	.0035	10	16	439	.333	.090
12-1	7.0	-13.7	20.7	.9715	.2368	1788	1736	423	6.40	27.30	74	.0679	78.0	12.4	.78	.007	10	8	425	1.38	.333
2	2.7	-10.1	12.8	.9845	.1754	1778	1750	312	8.42				89.5	13.4	.83	.003	6	9	309	1.06	.186
3	1.1	-9.6	10.7	.9860	.1668	1768	1742	295	9.72				96.2	15.4	.77	.008	17	11	301	.91	.158
4	-2.2	-10.2	8.0	.9842	.1771	1758	1730	312	12.23				107.8	16.4	.81	.004	10	13	309	.72	.129
5	-3.9	-10.5	6.6	.9833	.1822	1748	1720	319	14.05				115.4	17.9	.80	.005	14	14	319	.62	.116
6	-7.7	-11.7	4.0	.9792	.2008	1738	1701	352	18.15				131.0	19.6	.83	.003	10	15	347	.48	.097
7	-10.0	-12.2	2.8	.9751	.2215	1728	1680	383	21.4				142.8	21.5	.82	.004	17	15	385	.40	.091
8	-13.6	-15.0	1.4	.9659	.259	1718	1660	445	25.0				154.0	22.9	.83	.003	9	16	438	.34	.088
19-1	6.3	-15.7	22.0	.963	-.271	1794	1725	485	6.34	27.30	77	.0674	77.1	12.0	.75	.006	9	7	487	1.41	.389
2	5.6	-13.8	19.4	.971	.239	1782	1730	426	6.55				78.6	12.0	.80	.005	8	7	427	1.34	.332
3	5.1	-12.6	17.7	.976	.218	1770	1730	385	6.86				99.0	12.5	.78	.007	10	8	387	1.28	.281
4	4.0	-12.6	16.6	.976	.218	1758	1715	383	7.28				83.3	12.5	.82	.004	5	8	380	1.20	.266
5	2.8	-11.3	14.1	.981	.196	1745	1710	342	7.96				87.2	12.9	.84	.002	2	9	335	1.09	.214
6	2.6	-11.2	13.8	.981	.194	1734	1700	336	7.98				87.2	12.9	.84	.002	2	9	329	1.09	.210
7	2.5	-10.6	13.1	.983	.184	1722	1695	317	8.06				87.7	13.2	.82	.003	5	9	313	1.07	.198
8	2.2	-10.5	12.7	.983	.182	1710	1680	311	8.42				87.7	13.3	.82	.004	6	9	308	1.01	.186
9	7.2	-14.0	21.2	.970	.242	1698	1650	411	6.08				74.2	10.9	.85	.001	1	7	405	1.39	.339
10	9.4	-16.2	25.6	.960	.279	1686	1620	470	5.46				72.2	11.2	.80	.006	8	6	472	1.51	.440
26-1	10.3	-17.3	27.6	.955	.297	1791	1710	532	5.67	27.30	63	.0693	72.5	11.3	.80	.006	7	7	532	1.53	.478
2	10.0	-16.8	26.8	.956	.289	1778	1700	513	5.46				71.9	11.1	.80	.006	7	7	513	1.58	.477
3	18.2	-14.9	23.1	.966	.257	1765	1700	453	5.98				74.5	11.6	.80	.006	7	7	453	1.44	.385
4	6.6	-13.8	20.4	.971	.239	1752	1700	418	6.34				76.8	12.2	.78	.007	10	7	421	1.36	.338
5	4.8	-12.5	17.3	.976	.216	1739	1700	375	7.12				81.4	12.5	.81	.005	8	8	375	1.21	.268
6	5.6	-11.5	15.1	.978	.199	1726	1690	344	7.10				84.0	13.1	.80	.006	9	9	344	1.12	.228
7	1.5	-10.3	11.8	.985	.179	1713	1690	307	9.20				93.0	14.1	.82	.004	0	10	303	.93	.168
8	.7	-10.3	9.6	.984	.179	1700	1670	304	11.85				105.0	15.2	.86	.0	0	12	292	.74	.131
9		-12.5		.976	.216	1687	1650	365	17.02				126.0	18.5	.84	.002	-6	15	356	.49	.103
10		-14.9		.966	.257	1674	1620	430	24.05				148.0	20.4	.90	-.004	-15	16	399	.34	.084
27-2	9.2	-15.7	24.9	.963	.271	1786	1720	483	5.82	27.30	64	.0691	73.5	11.2	.81	.005	5	7	481	1.50	.416
3	9.9	-16.2	26.1	.960	.279	1774	1700	495	5.67				73.5	11.9	.77	.008	9	7	497	1.53	.449
4	8.3	-14.8	23.1	.967	.255	1762	1700	449	5.98				74.5	12.4	.75	.010	15	7	457	1.45	.379
5	7.0	-13.6	20.6	.972	.235	1750	1700	411	6.40				77.0	12.7	.75	.010	16	7	420	1.35	.334
6	4.5	-11.3	15.8	.981	.196	1738	1710	340	7.54				83.7	14.0	.74	.011	21	9	352	1.15	.237
7	1.3	-9.9	11.8	.984	.172	1726	1700	297	9.22				93.0	15.2	.76	.009	20	10	307	.93	.170
8	-2.3	-10.5	8.2	.983	.182	1714	1680	311	13.88				113.6	18.6	.75	.010	34	13	332	.61	.122
9	-8.5	-12.5	4.0	.976	.216	1702	1660	368	21.00				138.5	22.1	.75	.007	34	15	387	.40	.094
28-1	8.1	-14.8	22.9	.967	.255	1819	1760	463	6.14	27.30	65	.0690	76.2	11.2	.84	.002	1	7	457	1.46	.378
2	6.8	-13.3	20.1	.973	.233	1811	1760	422	6.45				78.0	11.5	.84	.002	0	7	416	1.39	.324
4	2.4	-10.5	12.9	.983	.182	1795	1760	327	8.74				91.0	13.0	.86	.0	0	10	317	1.02	.184
5	.3	-10.1	10.9	.985	.175	1787	1760	313	9.88				96.6	14.0	.86	.0	0	13	302	.91	.156
6	-1.9	-10.1	8.2	.985	.175	1779	1750	311	12.38				108.0	15.5	.86	.0	0	13	298	.72	.122
7	-4.2	-11.2	7.0	.981	.194	1771	1720	344	14.57				117.1	16.7	.87	-.001	-2	14	328	.61	.115
8	-7.8	-12.5	4.7	.976	.216	1763	1720	381	18.93		Table		134.	18.7	.88	-.002	-6	14	359	.46	.097
9	-14.1	-16.0	1.9	.961	.276	1755	1685	485	27.30		(continued on next page)		161.	22.0	.90	-.004	-20	16	449	.31	.083
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22

McDONNELL GLIDE TESTS

all negative

Slots open, flaps neutral   Slots open and flaps neutral

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
29-1	8.4	-15.3	23.7	0.965	0.264	1827	1760	482	5.98	27.30	69	0.0684	74.0	11.2	0.82	0.004	5	7	480	1.50	0.408
2	6.3	-13.1	19.4	.974	.227	1819	1770	413	6.76				78.8	11.7	.83	.003	5	8	410	1.33	.308
3	4.6	-11.5	16.1	.980	.199	1811	1770	360	7.54				83.2	12.9	.80	.006	8	8	360	1.19	.243
4	3.2	-10.2	13.4	.984	.177	1803	1775	319	8.43				88.0	13.4	.82	.004	6	9	316	1.07	.191
5	.6	-10.0	10.6	.985	.174	1795	1770	312	10.04				97.0	14.2	.85	.001	2	12	302	.90	.153
6	-2.5	-10.6	8.1	.983	.184	1787	1750	328	13.00				109.2	15.5	.87	-.001	-3	13	312	.68	.122
7	-4.1	-11.4	7.3	.981	.198	1779	1740	352	14.41				115.0	16.9	.85	.001	3	14	341	.61	.121
8	-7.8	-12.8	5.0	.975	.222	1771	1730	393	18.58				130.5	18.5	.87	-.001	-3	15	375	.47	.103
9	-12.7	-15.3	2.6	.965	.264	1763	1700	465	26.32				155.5	22.4	.86	.0	0	16	349	.33	.087
30-1	8.9	-15.4	24.3	.964	.266	1786	1720	474	5.82	27.30	66	.0689	74.0	11.4	.81	.005	6	7	473	1.50	.413
2	6.9	-13.3	20.2	.973	.230	1780	1730	409	6.23				77.0	12.1	.79	.007	9	7	411	1.40	.332
3	5.1	-12.4	17.5	.977	.215	1774	1730	381	6.92				81.0	12.1	.83	.003	3	7	377	1.28	.280
4	3.9	-10.9	14.8	.982	.189	1768	1740	334	7.70				85.1	12.9	.82	.004	6	9	331	1.15	.219
5	2.5	-10.4	12.9	.984	.181	1762	1730	319	8.53				89.6	13.1	.85	.001	2	9	312	1.03	.186
6	.8	-9.9	10.7	.985	.172	1756	1730	311	9.57				95.0	14.1	.83	.003	4	10	305	.92	.158
7	-2.6	-10.2	7.6	.984	.181	1750	1720	316	12.7				109.5	15.3	.88	-.002	-5	13	298	.69	.119
8	-4.7	-10.8	6.1	.982	.187	1744	1710	326	14.6				117.5	16.9	.86	.0	0	14	312	-.53	.109
9	-8.5	-12.7	4.2	.976	.220	1738	1700	382	19.1				134.0	18.9	.88	-.002	-6	15	361	.45	.096
15-1	9.3	-15.0	24.3	.966	.259	1780	1720	460	5.72	27.30	70	.0683	73.6	12.0	.76	.010	13	7	454	1.53	.404
3	8.4	-14.1	22.5	.970	.244	1750	1695	427	5.72				73.6	11.9	.77	.009	11	7	423	1.51	.377
5	18.8	-14.6	23.4	.968	.252	1720	1665	433	5.62				72.9	12.2	.75	.011	15	7	425	1.51	.385
16-3	8.7	-14.7	23.4	.967	.254	1832	1770	465	5.77	27.30	75	.0676	73.6	12.0	.76	.010	13	6	458	1.56	.404
5	8.8	-14.9	23.7	.965	.257	1808	1745	464	5.62				71.3	12.4	.71	.014	18	6	452	1.58	.409
7	7.6	-14.1	21.7	.970	.244	1784	1730	435	6.08				73.6	12.2	.75	.011	15	6	426	1.45	.356

Slots closed and flaps down   Slots closed and flaps down

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
23-1	-.6	-12.5	11.9	.976	.216	1876	1830	405	6.97	27.30	70	.0683	81.0	12.8	.78	-.007	11	8	408	1.34	.298
3	.3	-12.8	12.5	.975	.222	1850	1800	411	6.86				80.5	13.0	.77	-.008	13	8	416	1.33	.309
4	-4.7	-11.5	6.8	.980	.199	1837	1800	366	8.06				87.2	13.1	.82	-.004	5	9	362	1.14	.229
6	-10.3	-12.3	2.0	.977	.213	1811	1770	386	11.85				105.7	15.9	.83	.003	7	12	381	.76	.164
24-3	.8	-13.3	14.1	.973	.230	1780	1730	409	6.40	27.30	71	.0682	78.0	12.9	.76	.010	15	7	417	1.38	.332
6	-10.2	-12.0	1.8	.977	.208	1750	1710	364	11.5				104.5	15.5	.83	.003	5	12	357	.75	.157
7	-12.6	-13.0	.4	.974	.225	1740	1700	392	13.6				113.6	17.0	.83	.003	8	13	387	.64	.145
8	-15.8	-14.4	-1.4	.969	.249	1730	1660	430	16.4				125.0	18.9	.82	.004	11	14	427	.52	.132
10	-20.6	-17.4	-3.2	.954	.299	1710	1630	511	24.1				151.2	22.7	.83	.003	14	16	509	.34	.107
1	.5	-12.5	13.0	.975	.216	1800	1760	389	6.55				78.9	12.9	.76	-.010	15	8	396	1.37	.308
2	.4	-12.6	13.0	.976	.218	1790	1740	389	6.55				78.9	12.9	.76	.010	15	8	396	1.35	.306
4	-4.0	-11.2	7.2	.981	.194	1770	1740	343	7.96				87.0	13.1	.81	.005	7	9	341	1.11	.218
5	-6.2	-11.4	5.2	.980	.198	1760	1720	348	8.69				90.8	14.1	.80	.006	11	10	349	1.00	.204
9	-19.1	-16.2	2.9	.960	.282	1720	1650	485	20.6				140.0	20.5	.85	.001	4	15	374	.41	.116
33-1	-3.4	-11.9	8.5	.978	.206	1800	1760	371	7.80	27.30	71	.0682	86.	12.4	.86	.0	0	9	362	1.15	.236
2	-5.3	-12.1	6.8	.978	.210	1791	1750	376	8.42				89.	12.7	.86	.0	0	9	367	1.06	.222
3	-6.5	-12.2	5.7	.977	.211	1782	1740	376	9.10				93.	13.1	.88	-.002	-3	10	363	.97	.203
4	-7.4	-12.1	4.7	.978	.210	1773	1740	372	9.42				94.	13.7	.85	-.001	-2	10	364	.94	.197
5	-9.0	-12.7	3.7	.975	.220	1764	1720	388	10.4				99.	14.1	.87	-.001	-1	11	375	.84	.183
6	-10.1	-12.8	2.7	.975	.221	1755	1710	388	11.0				102.	15.0	.84	-.002	-4	12	380	.79	.175
7	-12.2	-13.3	1.1	.973	.230	1746	1700	401	12.5				108.	15.6	.86	.0	0	13	388	.69	.158
8	-14.1	-14.3	.2	.971	.247	1737	1690	429	13.6				113.	16.1	.87	-.001	-2	13	414	.63	.155
9	-15.8	-15.1	-.7	.966	.261	1728	1670	450	15.2				120.	17.2	.86	.0	0	14	436	.56	.146
10	-18.3	-16.3	-2.0	.961	.281	1719	1650	483	17.3				128.	19.2	-.82	.004	0	15	481	.48	.141
23-5	-7.2	-11.7	4.5	.979	.203	1824	1790	371	9.72	27.30	70	.0683	95.7	14.0	.84	.002	3	10	364	.94	.191
7	-13.1	-12.9	-.2	.975	.223	1798	1750	402	14.7				117.8	17.0	.85	.001	2	14	390	.80	.134

Slots open and flaps down   Slots open and flaps down

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
15-2	6.3	-16.2	22.5	.961	.279	1765	1695	492	4.63	27.30	70	.0683	66.3	10.9	.76	.010	11	6	497	1.86	.545
4	6.6	-16.3	22.9	.960	.281	1735	1665	487	4.42				64.8	11.2	.72	-.013	15	5	497	1.91	.572
16-2	6.4	-16.2	22.6	.960	.279	1846	1770	515	4.63	27.30	75	.0676	66.0	11.6	.70	.015	18	4	529	1.95	.580
4	6.4	-16.1	22.5	.961	.277	1820	1750	504	4.63				66.0	11.7	.70	.015	19	4	519	1.92	.570
6	6.4	-16.2	22.6	.960	.279	1796	1725	502	4.63				66.0	11.7	.70	.015	19	4	517	1.90	.570
8	6.5	-16.2	22.7	.960	.279	1772	1700	495	4.47				64.8	11.6	.69	.016	19	4	510	1.94	.580
17-1	.8	-13.4	14.2	.973	.232	1853	1805	430	5.77	27.30	72	.0681	73.7	12.4	.74	.012	17	7	440	1.59	.388
2	-4.7	-11.8	7.1	.979	.204	1844	1805	377	7.64				84.8	14.0	.75	.011	20	9	388	1.20	.259
3	-12.0	-14.1	2.1	.970	.244	1835	1780	448	11.70				104.5	15.4	.85	.001	2	12	478	.77	.208
4	-7.4	-12.3	4.9	.977	.213	1826	1790	389	8.89				91.5	15.6	.74	.012	28	10	407	1.02	.233
5	-14.5	-14.9	.4	.966	.257	1817	1755	467	14.25				116.0	17.9	.80	.006	77	14	470	.63	.168
6	-.7	-12.5	11.8	.976	.216	1808	1765	391	6.19				76.4	12.4	.76	.010	13	7	397	1.45	.327
7	-4.7	-12.0	7.3	.978	.208	1799	1760	374	7.64				84.8	13.7	.77	.009	15	9	380	1.17	.254
8	-7.8	-12.5	4.7	.976	.216	1790	1750	386	9.10				92.6	14.6	.78	.008	14	10	390	.98	.218
9	-11.9	-13.6	1.7	.972	.235	1781	1730	418	11.70				104.5	16.7	.78	.008	20	12	426	.75	.185
10	-14.5	-15.2	.7	.965	.262	1772	1710	464	14.40				116.5	18.1	.80	.006	18	14	468	.60	.165
18-1	.9	-12.2	11.3	.974	.211	1789	1745	378	6.34	27.30	73	.0679	77.3	12.2	.78	.007	10	6	382	1.40	.306
2	-5.0	-11.8	6.8	.979	.205	1780	1740	364	7.10				85.7	13.7	.77	.008	14	9	368	1.14	.240
3	-9.3	-12.7	3.4	.976	.220	1771	1730	389	9.88				96.4	14.7	.81	.005	10	11	388	.89	.201
4	-12.5	-14.1	1.6	.970	.244	1762	1710	429	11.55				104.2	16.4	.79	.006	16	12	433	.75	.191
5	-14.5	-14.5	.0	.968	.250	1753	1700	441	13.88				114.5	17.7	.80	.006	18	14	445	.67	.151
6	-1.6	-11.8	10.2	.979	.205	1744	1710	357	6.55				78.5	12.5	.78	.007	11	7	361	1.33	.280
7	-6.0	-12.3	6.3	.977	.213	1735	1700	370	7.65				84.9	13.2	.80	.006	9	9	370	1.13	.248
8	-9.2	-12.8	3.6	.975	.221	1726	1680	382	9.57				95.0	14.9	.80	.006	11	11	382	.89	.285
9	-12.4	-14.1	1.7	.970	.244	1717	1665	418	11.70				105.5	16.2	.80	.006	12	12	418	.72	.182
10	-15.4	-15.4	.0	.964	.266	1708	1645	455	14.90				117.0	17.9	.81	.005	13	14	454	.58	.160
20-1	6.3	-16.6	22.9	.958	.286	1790	1720	512	4.63	27.30	78	.0673	66.5	10.8	+.76	.010	10	5	517	1.89	.568
2	7.1	-16.5	23.6	.959	.284	1777	1705	505	4.63				66.5	10.8	.76	.010	10	5	510	1.88	.582
3	4.0	-14.8	18.8	.967	.255	1764	1705	449	5.15				70.0	10.7	.81	.005	5	9	448	1.69	.444
4	4.3	-15.2	19.5	.965	.263	1751	1690	460	5.15				70.0	10.7	.81	.005	5	6	459	1.67	.455
5	2.8	-12.6	15.4	.976	.218	1738	1700	380	5.62				73.2	11.1	.81	.005	5	7	378	1.54	.343
6	.0	-12.0	12.0	.978	.208	1725	1690	359	5.93				75.2	11.2	.82	.004	4	6	356	1.45	.306
7	2.2	-13.0	15.2	.974	.225	1712	1670	385	5.46				72.2	11.0	.81	.005	4	6	384	1.55	.358
8	.4	-12.5	12.9	.976	.216	1699	1660	366	5.77				74.2	11.5	.80	.006	7	7	366	1.46	.322
9	7.7	-17.0	24.7	.956	.292	1686	1610	491	4.32				64.2	11.5	.76			5	495	1.91	.583
31-1	3.5	-14.9	18.4	.966	.257	1794	1730	460	5.36	27.30	70	.0683	71.	10.7	.82	.004	4	6	458	1.63	.435
2	2.5	-13.5	16.0	.972	.233	1787	1730	415	5.67				73.	11.4	.80	.006	7	7	415	1.55	.372
3	1.3	-12.2	10.9	.978	.211	1780	1740	376	6.45				83.	11.6	.89	-.003	-4	7	365	1.37	.288
4	2.0	-11.7	19.7	.979	.203	1773	1730	360	6.76				80.	12.0	.82	.004	5	8	357	1.30	.261
5	6.8	-12.2	5.4	.977	.211	1766	1730	372	8.48				89.	13.2	.82	.004	6	9	369	1.04	.214
6	9.9	-13.1	3.2	.974	.227	1759	1710	398	10.25				110.	14.0	.87	-.001	-2	12	384	.85	.119
7	13.0	-13.8	.8	.971	.239	1752	1700	418	12.90				110.	15.4	.89	-.003	-7	13	398	.67	.157
8	15.2	-15.1	-.1	.966	.261	1745	1690	455	14.77				118.	16.9	.87	-.001	-1	14	440	.58	.150
9	19.6	-17.6	-2.0	.953	.302	1738	1650	525	19.15				134.	19.0	.87	-.001	-3	15	507	.44	.135
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22

TABLE II

Performance Characteristics of McDonnell Airplane

	Slots closed, flaps neutral	Slots open, flaps neutral	Slots closed, flaps down	Slots open, flaps down
High speed	91.4 m.p.h.	84.8 m.p.h.		
Minimum speed in glide (Landing speed)	60 m.p.h.	48 m.p.h.	51 m.p.h.	43 m.p.h.
Angle of attack at landing speed	16.2°	27.0°	14.2°	23.7°
Angle of glide at landing speed	13.0°	17.3°	13.5°	17.2°
Vertical velocity at landing speed	19.8 ft./sec.	21.0 ft./sec.	17.5 ft./sec.	18.6 ft./sec.
Minimum speed in level flight (Take-off speed)	55 m.p.h.	44 m.p.h.	46 m.p.h.	40 m.p.h.
Angle of attack at take-off speed	13.0°	24.0°	11.3°	16.7°
Minimum angle of glide	9.8°	9.8°	11.5°	12.5°
Speed range	1.5	1.9	1.8	2.1

With Slots Automatic and Flaps Neutral

Maximum rate of climb	310 ft./min.
Maximum angle of climb	3.4°

Slot Operation

	Power on flaps neutral	Power on flaps down
Slots start to open	5.8° angle of attack	4.1° angle of attack
Slots fully open	10.1° " " "	8.7° " " "
Slots start to close	9.4° " " "	8.4° " " "
Slots fully closed	5.5° " " "	3.6° " " "

Fig. 1

Fig. 1 Three-view drawing of the McDonnell airplane

Fig. 2 Front view of the McDonnell airplane

Fig. 3 Three-quarter rear view of the McDonnell airplane

Fig. 4 Side view of the McDonnell airplane with the slots open and flaps down

Fig. 5   M-6 wing section equipped with slots and flaps

Fig. 5

Fig. 6 Characteristic curves for the McDonnell airplane with
slots closed and flaps neutral.

Fig. 7 Polar curve for the McDonnell airplane
with slots closed and flaps neutral

Fig. 8   Characteristic curves for the McDonnell airplane with slots open and flaps neutral

Fig. 9   Polar curve for the Mc Donnell airplane with slots open
   and flaps neutral

Fig. 10 Characteristic curves for the Mc Donnell airplane with slots closed and flaps down

Fig. 11   Polar curve for the Mc Donnell airplane with slots closed
          and flaps down

Fig. 12 Characteristic curves for the McDonnell airplane with slots open and flaps down

Fig. 13 Polar curve for the McDonnell airplane with slots
         opon and flars down

Fig. 14 Characteristic curves for the McDonnell airplane for all
conditions of slots and flaps tested

Fig. 15

Fig. 15 Polar curves for the McDonnell airplane for all
conditions of slots and flaps tested